

5" Fireproof Ceiling Speaker FCS-56CEN

Features:

- ✓ Compliant with the EN54-24 standards fireproof ceiling speaker
- ✓ Built-in 100v/70v transformer for PA & VA system
- ✓ In-ceiling fast installation type loudspeaker
- ✓ 5" full range speaker unit
- ✓ Power taps 1.5W/3W/6W @100V
- ✓ With metal fire dome for fireproof applications
- ✓ Aluminum grille, metal baffle and fire dome
- ✓ Paint in white color
- ✓ Fireproof version design of ceramic terminal, thermal fuse, fire dome and fire-resistant cable
- ✓ Fast installation by its three spring clips



EN54-24

Specifications:

Model	FCS-56CEN
Power Taps @100V	6W/3W/1.5W
SPL(1W/1M),peak	98.5dB
Frequency Response	110-14.5KHz (-10dB)
Finish	Baffle & Grille: Steel, White; Cover: Steel, white
Speaker Driver	5" x 1 full range paper cone
Dispersion -6dB, 500Hz	h = 180°, v = 180°
Dispersion -6dB, 1KHz	h = 160°, v = 160°
Dispersion -6dB, 2KHz	h = 130°, v = 130°
Dispersion -6dB, 4KHz	h = 90°, v = 90°
Cutout Size	175mm
Dimensions	200 x 105mm
Weight	0.9Kg
Mounting	Spring-clip

Side View & Dimensions:



SPL VS Frequency Diagrams:

